



5300 Beethoven Street, Los Angeles, CA 90066  
 TEL: (310)306-5556 • FAX: (310)577-9887  
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

**MODEL 4046-001**  
**1100 - 1300 MHz**  
**400 WATTS**  
**LINEAR POWER RF AMPLIFIER**

**Solid State  
 Band-specific High  
 Power RF Amplifier**

The 4046-001 is a 400 Watt band-specific amplifier that covers the 1100 – 1300 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 4046-001 comes with an extended

	Parameter	Specification @ 25 °C
<b>Electrical</b>		
1	Frequency Range	1100 – 1300 MHz
2	Saturated Output Power	400 Watts typical
3	Power Output @ 1dB Comp.	320 Watts min
4	Small Signal Gain	+57 dB min
5	Small Signal Gain Flatness	± 1.5 dB max
6	IP <sub>3</sub>	+65 dBm typical
7	Input/Output VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 320 Watts
9	Spurious Signals	< -60 dBc typical @ 320 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	2500 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input with AC on or OFF	27 dBm max.
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
<b>Mechanical</b>		
16	Dimensions	19" x 8.75" x 24"
17	Weight	100 lb. max
18	Connectors	Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
<b>Environmental</b>		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

**CIRCUIT PROTECTIONS**

- ◇ Infinite Load VSWR using an Isolator
- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage

