



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)821-7413
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 4064-002
2.0 - 2.65 GHz
60 WATTS
LINEAR POWER RF AMPLIFIER

**Solid State
 Band-Specific High
 Power RF Amplifier**

The 4064-002 is a 60 Watt broadband amplifier that covers the 2.0 – 2.65 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 4064 comes with an extended multiyear warranty.

	Parameter	Specification @ 25° C
Electrical		
1	Frequency Range	2.0 – 2.65 GHz
2	Saturated Output Power	60 Watts rated
3	Power Output @ 1dB Comp.	45 Watts min
4	Small Signal Gain	+49 dB min
5	Small Signal Gain Flatness	± 1.5 dB max
6	IP ₃	+57 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 45 Watts
9	Spurious Signals	< -60 dBc typical @ 45 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	600 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	+10 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	A/AB
Mechanical		
16	Dimensions	19" x 5.25" x 20"
17	Weight	48 lb. max
18	Connectors	Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
Environmental		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

CIRCUIT PROTECTIONS

- ◇ Thermal Overload
- ◇ Over Voltage and Current
- ◇ Over power protection
- ◇ VSWR protection

CIRCUIT CONTROL

- ◇ Standby
- ◇ Gain Control, 20dB range
- ◇ ALC control

CIRCUIT INDICATIONS

- ◇ Forward and Reflected power indication
- ◇ Gain Control, % selection
- ◇ Web browser interface (Ethernet)

ORDERING MODELS

- ◇ RE - Rear Panel model with Ethernet, RS232, and IEEE Interface
- ◇ FE - Front Panel model with Ethernet, RS232, and IEEE Interface

Specifications subject to change without notice.



RE Model Shown