

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5020-485

500 - 1000 MHz **200 WATTS** LINEAR POWER RF AMPLIFIER

Specification @ 25° C

Solid State **Broadband High Power RF Amplifier**

The 5020-485 is a 200 Watt broadband amplifier that covers the 500 - 1000 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and comthis amplifier ponents. achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5020-485 comes with an extended multiyear warranty.

<u>Electrical</u>		
1	Frequency Range	500 – 1000 MHz
2	Saturated Output Power	200 Watts typical
3	Power Output @ 1dB Comp.	100 Watts min
4	Small Signal Gain	+53 dB min
5	Small Signal Gain Flatness	<u>+</u> 1.5 dB max
6	IP ₃	+56 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 100 Watts
9	Spurious Signals	> -60 dBc typical @ 100 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	1250 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	0 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
<u>Mechanical</u>		
16	Dimensions	19" x 7.0" x 20"
17	Weight	60 lb. max
18	Connectors	Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
Environmental		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport
Specifications subject to change without notice		

<u>Parameter</u>

Specifications subject to change without notice.

CIRCUIT PROTECTIONS

- ♦ Thermal Overload
- ♦ Over Current
- ♦ Over Voltage

CIRCUIT INDICATIONS

- ♦ Forward Power
- ♦ Reflected power
- ♦ VSWR Fault
- ♦ Temp Fault
- ♦ Gain Setting (VVA) percentage

ORDERING MODELS

- ♦ RE F model with Ethernet, IEEE488 & RS-485
- ♦ FE R model with Ethernet, IEEE488 & RS-485



Date: