

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

## **MODEL 5141-043**

0.7 - 3.0 GHz 15 WATTS LINEAR POWER RF AMPLIFIER

## Solid State Broadband High Power RF Amplifier

The 5141-043 is a 15 Watt broadband amplifier that covers the 0.7 - 3.0 GHz frequency range. This small lightweight amplifier and utilizes Class A/AB linear power devices that provide 3<sup>rd</sup> excellent order an intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 5141-043 comes with an extended multiyear warranty.

♦ Thermal Overload

**ORDERING MODELS** 

- ♦ Over Current
- ◊ Over Voltage

<b>CIRCUIT</b>	P	PRO	TEC	TIONS

◊ R	<ul> <li>Rear Panel Connectors</li> </ul>
◊ F	- Front Panel Connectors
♦ RE	- R model w/Control Option

♦ RE - R model w/Control Option
♦ FE - F model w/Control Option

Electrical			
1	Frequency Range	0.7 – 3.0 GHz	
2	Saturated Output Power	15 Watts typical	
3	Power Output @ 1dB Comp.	12 Watts min	
4	Small Signal Gain	+43 dB min	
5	Small Signal Gain Flatness	<u>+</u> 2.0 dB max	
6	IP <sub>3</sub>	+51 dBm typical	
7	Input VSWR	2:1 max	
8	Harmonics	-20 dBc typical @ 12 Watts	
9	Spurious Signals	> -60 dBc typical @ 12 Watts	
10	Input/Output Impedance	50 Ohms nominal	
11	AC Input Power	200 Watts max	
12	AC Input	100 – 240 VAC, single phase	
13	RF Input	+10 dBm max	
14	RF Input Signal Format	CW/AM/FM/PM/Pulse	
15	Class of Operation	A/AB	
<u>Mechanical</u>			
16	Dimensions	19" x 3.5" x 18"	
17	Weight	30 lb. max	
18	Connectors RF In/Out and Sample Port	Type-N	
19	Grounding	Chassis	
20	Cooling	Internal Forced Air	
21	Sample Port	Forward Power (-43dB below Power)	
<b>Environmental</b>			
21	Operating Temperature	0° C to +50° C	
22	Operating Humidity	95% Non-condensing	
23	Operating Altitude	Up to 10,000' Above Sea Level	
24	Shock and Vibration	Normal Truck Transport	

Specifications subject to change without notice.

