



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)821-7413
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5300473

**20 - 1000 MHz
 VARIABLE VOLTAGE
 ATTENUATOR**

Solid State Broadband High Power RF Amplifier

The 5300473 is a variable voltage attenuator that covers the 20-1000MHz frequency range. This small and lightweight VVA can provide an excellent insertion loss and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this VVA has proven reliability.

Specifications subject to change without notice.

	Parameter	Specification @ 25° C
Electrical		
1	Frequency Range	20 – 1000 MHz
2	Attenuation	20dB typ.
3	Insertion Loss	-5.0 dB typ.
4	RF Input	+3dBm Max, 0dBm typ.
5	Input VSWR	2:1 max
6	Control Voltage	0-8.0 VDC Max 7.5VDC typ. for min Attenuation, 0VDC for Max Attenuation
7	Flatness	+/- 2.5dB
8	Input/Output Impedance	50 Ohms nominal
9	DC Input Current	750mA Max
10	DC Input	13 VDC nominal
Mechanical		
11	Dimensions	3.1" x 2.0" x 0.7"
12	Weight	
13	Connectors	SMA female
14	Grounding	Chassis
Environmental		
15	Baseplate Temperature	0° C to +50° C
16	Operating Humidity	95% Non-condensing
17	Operating Altitude	Up to 10,000' Above Sea Level
18	Shock and Vibration	Normal Truck Transport

