



5300 Beethoven Street, Los Angeles, CA 90066  
TEL: (310)306-5556 • FAX: (310)577-9887  
WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

## MODEL 5300636-012

**0.9 - 1.3 GHz**  
**120 WATTS**  
**LINEAR POWER RF AMPLIFIER**

### Solid State Broadband High Power RF Amplifier

The 5300636-012 is a 120 Watt broadband amplifier that covers the 0.9-1.3 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 5300636-012 comes with an extended multiyear warranty.

	Parameter	Specification @ 25° C
<b>Electrical</b>		
1	Frequency Range	0.9-1.3 GHz
2	Saturated Output Power	120 Watts typical
3	Power Output @ 1dB Comp.	80 Watts min
4	Small Signal Gain	+8 dB min
5	Gain Flatness	± 1.0 dB max
6	IP <sub>3</sub>	+59 dBm typical
7	Input / Output VSWR	2:1 max
8	Harmonics	-20 dBc min @ 80 Watts
9	Spurious Signals	> -60 dBc max @ 80 Watts
10	Input/Output Impedance	50 Ohms nominal
11	DC Input Current	30 Amps max
12	DC Input	13 VDC nominal
13	RF Input	+43 dBm
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	A/AB
<b>Mechanical</b>		
16	Dimensions	8.15" x 7.39" x 1.1"
17	Weight	4 lb. max
18	Connectors	SMA female input N-Type Output
19	Grounding	Chassis
20	Cooling	Adequate Heatsink Required
<b>Environmental</b>		
21	Baseplate Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.

