



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)577-9887
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5802031

1.8 - 2.0 GHz
150 WATTS

**Solid State
 Band-specific High
 Power RF Amplifier**

The 5802031 is a 100 Watt band-specific amplifier that covers the 1.8 – 2.0 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5802031 comes with an extended

	<u>Parameter</u>	<u>Specification @ 25° C</u>
<u>Electrical</u>		
1	Frequency Range	1.8 – 2.0 GHz
2	Instantaneous Bandwidth	60 MHz min
3	Saturated Output Power	150 Watts typical
4	Power Output @ 1dB Comp.	120 Watts min
5	Small Signal Gain	+53 dB min
6	Gain Flatness	± 1.0 dB max
7	IP ₃	+59 dBm typical
8	Input VSWR	2:1 max
9	Harmonics	-20 dBc typical @ 120 Watts
10	Spurious Signals	> -60 dBc typical @ 120 Watts
11	Input/Output Impedance	50 Ohms nominal
12	DC Input Current	32 Amps max
13	DC Input	13 VDC nominal
14	RF Input	+10 dBm max
15	RF Input Signal Format	CW/AM/FM/PM/Pulse
16	Class of Operation	A/AB
<u>Mechanical</u>		
17	Dimensions (w/Heatsink)	14.5" x 9.8" x 4.1"
18	Weight (w/Heatsink)	20 lb. max
19	Connectors	SMA female
20	Grounding	Chassis
21	Cooling	Adequate Airflow Required
<u>Environmental</u>		
22	Operating Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.



FEATURES:
 Heatsink and Fans Included (Not Shown)