



5300 Beethoven Street, Los Angeles, CA 90066
TEL: (310)306-5556 • FAX: (310)577-9887
WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5903039

20 - 1000 MHz
50 WATTS

Solid State Broadband High Power RF Amplifier

The 5903039 is a 50 Watt broadband amplifier that covers the 20 – 1000 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5903039 comes with an extended

| | Parameter | Specification @ 25° C |
|----------------------|--------------------------|------------------------------------|
| Electrical | | |
| 1 | Frequency Range | 20 – 1000 MHz |
| 2 | Saturated Output Power | 50 Watts typical |
| 3 | Power Output @ 1dB Comp. | 30 Watts min |
| 4 | Small Signal Gain | +22 dB min |
| 5 | Gain Flatness | ± 1.5 dB max |
| 6 | IP ₃ | +51 dBm typical |
| 7 | Input VSWR | 2:1 typical |
| 8 | Harmonics | -20 dBc typical @ 30 Watts |
| 9 | Spurious Signals | > -60 dBc typical @ 30 Watts |
| 10 | Input/Output Impedance | 50 Ohms nominal |
| 11 | DC Input Current | 16 Amps max |
| 12 | DC Input | 28 VDC nominal |
| 13 | RF Input | +27 dBm max |
| 14 | RF Input Signal Format | CW/AM/FM/PM/Pulse |
| 15 | Class of Operation | AB |
| Mechanical | | |
| 16 | Dimension | 9.8" x 8.0" x 4.3" (with heatsink) |
| 17 | Weight | 10 lb. max (with heatsink) |
| 18 | Connectors | SMA female |
| 19 | Grounding | Chassis |
| 20 | Cooling | Adequate Cooling Required |
| Environmental | | |
| 21 | Operating Temperature | 0° C to +50° C |
| 22 | Operating Humidity | 95% Non-condensing |
| 23 | Operating Altitude | Up to 10,000' Above Sea Level |
| 24 | Shock and Vibration | Normal Truck Transport |

Specifications subject to change without notice.



FEATURES:

* Heatsink Included (Not Shown)