



5300 Beethoven Street, Los Angeles, CA 90066

TEL: (310)306-5556 • FAX: (310)577-9779

WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5903064-001

100 kHz - 100 MHz

150 WATTS P_1 dB

Solid State Broadband High Power RF Amplifier

The 5903064-001 is a 150 Watt broadband amplifier that covers the 0.10 – 100 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5903064-001 comes with an extended

	Parameter	Specification @ 25° C
<u>Electrical</u>		
1	Frequency Range	0.10 – 100 MHz
2	Power Output @ 1dB Comp.	150 Watts min
3	Small Signal Gain	+16 dB min
4	Gain Flatness	± 1.5 dB max
5	IP ₃	+58 dBm typical
6	Input VSWR	2:1 max
7	Harmonics	-20 dBc typical @ 150 Watts
8	Spurious Signals	> -60 dBc typical @ 150 Watts
9	Input/Output Impedance	50 Ohms nominal
10	DC Input Current	20 Amps max
11	DC Input	28 VDC nominal
12	RF Input	+37 dBm
13	RF Input Signal Format	CW/AM/FM/PM/Pulse
14	Class of Operation	AB
<u>Mechanical</u>		
15	Dimensions (with Heatsink)	16" x 9.8" x 4"
16	Weight (with Heatsink)	20 lb. max
17	Connectors	SMA female
18	Grounding	Chassis
19	Cooling	Adequate Airflow Required
<u>Environmental</u>		
20	Operating Temperature	0° C to +50° C
21	Operating Humidity	95% Non-condensing
22	Operating Altitude	Up to 10,000' Above Sea Level
23	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.