


NO.	COMPONENTS	IMPEDANCE
1	SMA MALE RIGHT ANGLE	50 OHM
2	.141" HANDBENDABLE CABLE (= JYEBAO P/N .141SRF-W-P-50)	50 OHM
3	N FEMALE FOR BULKHEAD	50 OHM

SMA MALE
RIGHT ANGLE



1


2

3

N FEMALE
FOR BULKHEAD


GASKET

5/8-24UNEF-2A
1.9 [7.48] HEX



1.35
[5.31]

JYE BAO P/N	L CM (INCH)
A39N85-141S-15	15 (5.906)
A39N85-141S-30	30 (11.811)
A39N85-141S-50	50 (19.685)
A39N85-141S-100	100 (39.370)
A39N85-141S-150	150 (59.055)
A39N85-141S-200	200 (78.740)
A39N85-141S-XXX	CUSTOM LENGTH IN CM



MOUNTING HOLE

LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.	JYE BAO CO., LTD.	
	TAIPEI TAIWAN	
	DESCRIPTION	CABLE ASSEMBLY SMA PLUG R/A TO N JACK FOR BULKHEAD
	JYE BAO DRAWING NO.	A39N85-141S-XXX