


NO.	COMPONENTS	IMPEDANCE
1	SMA REVERSE POLARITY MALE RIGHT ANGLE	50 OHM
2	.085" HANDBENDABLE CABLE (= JYEBAO P/N .085SRF-W-P-50)	50 OHM
3	SMA REVERSE POLARITY FEMALE FOR BULKHEAD	50 OHM


SMA R/P MALE  
RIGHT ANGLE




2

SMA R/P FEMALE  
FOR BULKHEAD

3




1/4-36UN-2A  
0.8 [L.315] HEX  
1.1 [L.433] HEX



0.66  
[L.260]

JYE BAO P/N	L CM (INCH)
A69A95-85S-15	15 (5.906)
A69A95-85S-30	30 (11.811)
A69A95-85S-50	50 (19.685)
A69A95-85S-100	100 (39.370)
A69A95-85S-150	150 (59.055)
A69A95-85S-200	200 (78.740)
A69A95-85S-XXX	CUSTOM LENGTH IN CM



MOUNTING HOLE

LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.	<b>JYE BAO CO., LTD.</b> TAIPEI TAIWAN
	DESCRIPTION CABLE ASSEMBLY SMA R/P PLUG R/A TO SMA R/P JACK FOR BULKHEAD
	JYE BAO DRAWING NO. A69A95-85S-XXX