



NO.	COMPONENTS	IMPEDANCE
1	SMA REVERSE POLARITY MALE RIGHT ANGLE	50 OHM
2	.085" TIN PLATED SEMI-RIGID CABLE (TIN PLATED RG405)	50 OHM
3	SMA REVERSE POLARITY FEMALE FOR BULKHEAD	50 OHM

SMA R/P MALE
RIGHT ANGLE




2


SMA R/P FEMALE
FOR BULKHEAD



1/4-36UN-2A
0.8 [L.315] HEX
1.1 [L.433] HEX



JYE BAO P/N	L CM (INCH)
A69A95-85T-15	15 (5.906)
A69A95-85T-30	30 (11.811)
A69A95-85T-50	50 (19.685)
A69A95-85T-100	100 (39.370)
A69A95-85T-150	150 (59.055)
A69A95-85T-200	200 (78.740)
A69A95-85T-XXX	CUSTOM LENGTH IN CM



MOUNTING HOLE

<p>LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.</p>	<p>JYE BAO CO., LTD. TAIPEI TAIWAN</p>
	<p>DESCRIPTION CABLE ASSEMBLY SMA R/P PLUG R/A TO SMA R/P JACK FOR BULKHEAD</p>
	<p>JYE BAO DRAWING NO. A69A95-85T-XXX</p>